

YAPIFINE GOOP® PAH

Flexible Waterproofing Tape



Product Definition

Polypropylene based, flexible waterproofing tape.

Areas of Use

- Horizontal and vertical joints,
- Underneath the indoors tiles and ceramics,
- Water tank, swimming pool and parapet joints,
- Foundation-shear wall joints,
- Piping inlets, filter details,
- Filling rod holes,
- As a system together with YAPIFINE HYDRA waterproofing products.

Advantages

- Perfectly compatible with spread waterproofing products and ensures joint-free insulation.
- Compatible with cement-based products thanks to alkali resistance.

Technical Specifications

Appearance	White
Size	Width: 20 cm Thickness: 1 mm
Service Temperature	-60°C / +80°C
Elongation at Longitudinal Rupture	24 %

Latitudinal Rupture Elongation	160 %
Bursting Pressure	3 Bar Positive
UV Resistance	Minimum 500 hours
Pressurized Water Strength	≥ 1.5 Bar

* Hereby technical values and product application instructions are obtained in the wake of tests conducted in environment of +23±2°C temperature with relative humidity of %50±5. Higher temperatures will shorten the time span, while lower temperatures will extend it.

 Packaging	50 m roll in cardboard box
--	----------------------------

Surface Preparation

The surface should be cleaned of all residual materials such as dust, oil, dirt, paint, curing materials, bitumen and other foreign substances that would prevent adhesion.

Plasters that are not completely adhered to surface and weak particles should be cleaned prior to application.

Any defect on projected application surface should be repaired with YAPIFINE MEND POWER.

Application Information

Waterproofing material is applied on the joints and cracks and before it dries YAPIFINE GOOP PAH is laid on top of it.

To make sure it thoroughly connects with the waterproofing layer it is pressed against the layer with the help of a roller or a brush.

It should be paid attention to that there are no bumps on the tape.

The second layer is applied only after the waterproofing material has dried off, meaning that the tape will be left in between the layer applications.

The tape should not be moved or lifted up until the waterproofing mortar has completely hardened.

Application Conditions

Should not be applied to surfaces that were exposed to sunlight for too long or to surfaces that are too hot or frozen.

Should not be applied when the ambient temperature is not within the values of +5°C and +30°C.

The application area should be protected from the effects of wind and direct sunlight.

It should be paid attention to that the sharp and piercing objects do not damage the structure of the product before the application.

Shelf Life

The shelf life of the product is 24 months when it is stored on wooden pallets in a cool, dry and moisture free environment with an ambient temperature between +10°C and +25°C.

Safety Precautions

The operator should be wearing proper work attire, goggles, mask and protective gloves appropriate to work and worker safety regulations.

In case of contact with the eyes or accidental ingestion of the product seek immediate medical attention.

For further information on the safe handling of this product please read the Safety Data Sheet (SDS).