

ARSET LUB 20

FORMWORK RELEASE AGENT(FOR STEEL AND PLYWOOD FORMWORKS)

Product Definition

ARSET LUB 20 is a mineral oil based, mold release agent that provides easy separation of the molds from concrete and creates smooth concrete surfaces.

Technical Properties

Chemical base	Mineral oil
Color, Appearance	Transparent liquid
Density	0,97 ± 0,02 g/cm ³

Advantages

- It enables easy and fast separation of the mold from concrete.
- Provides easy cleaning of formwork.
- Provides smooth and clean concrete surface.
- Does not leave any stain on the formwork.
- Extends the life of the formwork
- Prevents stains on formwork.
- ARSET LUB 20 is solvent-free.

Uses

- Specially recommended for steel formwork.
- It can also be used for other mold systems such as plastic and plywood formworks.

Consumption Dosage

With 1 liter of ARSET LUB 20, 40-60 m² steel formwork and 20-50 m² plywood formwork can be coated.

Method of Application

ARSET LUB 20 should be applied 2-3 hours before the molding. It should be stirred thoroughly before application. It should be applied by spraying or with brush-roller Depending on absorption rate it can be applied once or twice for two layers.

Packaging

- 25 kg plastic drum
- 180 kg drum

Storage and Shelf Life

Must be stored at temperatures between +5°C and +35°C. Under proper storing conditions, the product's shelf life is 6 months from production date if kept in original packaging unopened and undamaged. Packaged products must be shaken before use.

Safety Measures

Use protective clothes, gloves, glasses and mask compatible with health and safety regulations during the application. Avoid direct contact with eyes and skin during storing and application, in case of contact wash off thoroughly with soap and water, if ingested seek medical attention immediately. Store away from all foodstuffs. Keep away from children. For detailed safety information please consult the product's Material Safety Data Sheet.

Responsibility: The information given in this technical data sheet is based on the applications carried out in our field of production and latest technological developments. YAPICHEM KİMYA SAN. A.Ş. is only responsible for the quality of product. YAPICHEM KİMYA SAN. A.Ş. cannot be responsible for the results due to the wrong use of the product and/or apart from the written recommendations regarding the area of use and application method. This technical data sheet makes the prior issues void.