

YAPIFINE COOL® PRIME

Decorative Plaster Primer



Product Definition

Acrylic copolymer emulsion based plaster primer with high adhesive strength and filling, offering high coverage property for interior and exterior walls.

Areas of Use

- Horizontal and vertical applications,
- Before cement and especially gypsum-based thin plaster applications,
- In order to increase adherence before decorative plaster on insulating applications,
- Before plaster on former surfaces.

Advantages

- Ready-to-use.
- High adherence.
- Prevents rapid water loss of mortar when applied before cement-based coatings.
- White, with high covering feature.
- Odourless.
- Safely applicable indoors as it is water-based.

Technical Specifications

Appearance	White liquid
Density	1.55 kg/L ± 0.03
pH	7 – 9
Pot Life	~2 hours

Application Temperature	Between +5°C and +30°C
Dry Time (+20°C)	1 hour
Through-dry	6 hours

* Hereby technical values and product application instructions are obtained in the wake of tests conducted in environment of +23±2°C temperature with relative humidity of %50±5. Higher temperatures will shorten the time span, while lower temperatures will extend it.

 Packaging	25 kg plastic drum
--	--------------------

 Consumption	100-150 g/m ² per coat
--	-----------------------------------

Surface Preparation

The surface should be cleaned of all residual materials such as dust, oil, dirt, paint, curing materials, bitumen and other foreign substances.

Application Information



Mix with a low-speed mixer in a clean container, or in its package for at least 3 minutes. Apply to the surface by brush, roller or with a spray.

Application Conditions

Should not be applied when the ambient temperature is not within the values of +5°C and +35°C.

The application area should be protected from the effects of wind and direct sunlight.

Avoid application where there is frost or there is a risk of frost.

Avoid application where there is a risk of frost in the first 24 hours after the application or in areas open to direct sunlight or wind.

Surfaces that are too hot must be wetted before the application.

The application surface should be protected from rain until it sets.

Do not add any other substances that are not provided in the application manual.

The final consumption amount might vary depending on application conditions and surface characteristics.

Shelf Life

The shelf life of the product is 12 months when it is stored on wooden pallets in a cool, dry and moisture free environment with an ambient temperature between +10°C and +25°C.

Safety Precautions

The operator should be wearing proper work attire, goggles, mask and protective gloves appropriate to work and worker safety regulations.

In case of contact with the eyes, rinse with plenty of water before seeking immediate medical attention.

Rinse with plenty of water in case of contact with the skin.

For further information on the safe handling of this product please read the Safety Data Sheet (SDS).